


CORRUGATED TUBING

Narva's range of UV resistant corrugated tubing and fittings offers an efficient and professional solution for protecting wiring from the elements.

Select from polypropylene split sleeve tubing for general applications or non-split nylon tubing for heavy-duty, high temperature environments. With excellent chemical resistance nylon tubing is suitable for applications including dangerous goods vehicles and the mining industry.



PART No.	LENGTH PER BAG/SPOOL (metres)	DESCRIPTION	TUBE SIZE (nominal mm)	INTERNAL DIAMETER (mm)
CORRUGATED SPLIT SLEEVE TUBING				
56707-3*	3	Manufactured of black U.V. resistant, fire-retardant polypropylene Operating temperature -20°C to +90°C 	7	7.0mm
56707	10			
56708	30			
56709	200			
56710-3*	3		10	9.7mm
56710	10			
56711	30			
56712	125			
56713-3*	3		13	12.6mm
56713	10			
56714	30			
56715	75			
56716-3*	3		16	16.3mm
56716	10			
56717	30			
56718	50			
56720	10		20	21.1mm
56721	30			
56722	50			
56723	5		23	23.0mm
56724	30			
56725	50			
56729	3	29	29.0mm	
56730	10			
56731	40			
56736	5	36	36.0mm	
56737	25			
56748	5	48	48.0mm	
56749	25			

*Denotes Retail Packs