

NEW PRODUCT RELEASE

GEN III LED Performance Globes



FEATURES

- Up to 300% brighter than halogen globes*
- 6000Lm per kit at 5700°K for ideal visibility
- Adjustable LED orientation ensures precise beam control
- More distance 60 meter longer beam (low beam)
- More reliable 30x more life than halogen





*More light compared to a standard globe

GEN III LED Performance Globes

Performance Characteristics

- 300% more light on the road with a 60 metre longer beam when compared to a standard halogen globe.
- Up to 30x more life than a standard halogen globe making L.E.D a 'fit and forget' option for any suitable vehicle.
- No filament or moving parts make these globes ideal for rough terrain. Shock and vibration resistant to international standards (IEC 60068-2-64).





EMC Protected

Adjustable globe orientation

Aviation grade 6063 aluminium heat sink

External driver supplied



Shock & vibration resistant

PART No.	DESCRIPTION	BARCODES	AVAILABILITY	SUPERSEDES P/NO.
		Dratoobed		
18441	H1 12/24V LED CONVERSION KIT	9314464180354 (1)	Ex Stock	18401
		19314464180351 (20)		
18444	H4 12/24V LED CONVERSION KIT	9314464180361 (1)	Ex Stock	18404
		19314464180368 (20)		
18445	HB3 12/24V LED CONVERSION KIT	9314464180378 (1)	Ex Stock	18405
		19314464180375 (20)		
18446	HB4 12/24V LED CONVERSION KIT	9314464180392 (1)	Ex Stock	18406
		19314464180399 (20)		
18447	H7 12/24V LED CONVERSION KIT	9314464180408 (1)	Ex Stock	18407
		19314464180405 (20)		
18448	H8/9/11 12/24V LED CONVERSION KIT	9314464180439 (1)	Ex Stock	18411
		19314464180436 (20)		
18450	HIR2 12/24V LED CONVERSION KIT	9314464180453 (1)	Ex Stock	18412
		19314464180450 (20)		