## NAEVA®

## SPECIFICATIONS EX2 3" DOUBLE ROW LED POD LIGHT 72810











@ 1 LUX

CUS

HARNESS FREE

**DESCRIPTION** 

EX2's hybrid beam provides outstanding width and distance, without dark spots or hot spots, ensuring exceptional clarity in the dark. Revolutionary internal switching (patent pending) means no harness is required. A relay will be required for negatively switched vehicles. Making for the easiest wiring on the market and eliminating the need to wire these components through the firewall. Check local laws for your state. EX2's are built to last; sealed to IP68 & IP69K, with hard-coated polycarbonate lens, composite mounting brackets, stainless steel mounting hardware and a 7 year warranty.

| Raw Lumens                               | 1360Lm                      |
|--|-----------------------------|
| Effective Lumens                         | 1025Lm                      |
| Beam Distance                            | 195m @ 1lux                 |
| Beam Width                               | 16m @ 1lux                  |
| Colour Temperature                       | 5700K ±5%                   |
| Colour Rendering Index (CRI)             | 70                          |
| Height                                   | 90.8                        |
| Depth                                    | 73.5                        |
| Width                                    | 102                         |
| Weight                                   | 1170g ±10%                  |
| Cable                                    | 0.5m                        |
| Housing                                  | Pressure die-cast aluminium |
| Lens Material                            | Hard coated polycarbonate   |
| Lens Protector                           | Black ABS                   |
| Bracket                                  | Nylon + 30% Glass-Filled    |
| Input Voltage                            | 9-33V DC                    |
| Current Raw<br>(@13.5V/@28V)<br>Per Lamp | 1.11/0.53                   |

| LED's                    | 4  |
|--------------------------|--|
| LED Spec                 | 5W CREE LED  |
| Protection               | Reverse Polarity Protection, Over and Under Voltage Protection   |
| IP Rating                | IP68 & IP69K   |
| Operating<br>Temperature | -40 - +60°   |
| ECE R10                  | ✓  |
| RCM                      | ✓  |
| Warranty                 | 7 Years  |
| Wiring                   | Red - Positive<br>Yellow - High Beam Trigger<br>Black - Negative   |
| <b>Country of Origin</b> | China  |
| Kit Includes             | 1 x 3" Double Row Pod Light 1 x Black Lens Protector 2 x Colour Trims (Electric Blue - fitted on lamp/Slate Grey - in box) 1 x Wiring Pigtail Lead Product Instructions S/S Hardware |



