## NAFVA®

## SPECIFICATIONS EX2R 10" SINGLE ROW LED LIGHT BAR





72831









## **DESCRIPTION**

EX2R's feature ADR Approved white front position lights with RGB technology, which when paired with the EX2R Bluetooth Controller, offer a choice of 48 colours. With a hybrid beam that provides exceptional width and distance, without dark spots or hot spots, ensuring extraordinary clarity in the dark.Revolutionary internal switching (patent-pending) means there is no need for a harness. Sealed to IP68 & IP69K standards, equipped with hard-coated polycarbonate lenses, composite mounting brackets, stainless steel hardware, and backed by a robust 7-year warranty, the EX2R's are built for long-lasting performance.

Raw Lumens	2720Lm
Effective Lumens	2235Lm
Beam Distance	284m @ 1lux
Beam Width	34m @ 1lux
Colour Temperature	5700K ±5%
Colour Rendering Index (CRI)	70
Height	71
Depth	63.5
Width	268
Weight	884g ±10%
Cable	2m
Housing	Pressure die-cast aluminium
Lens Material	Hard coated polycarbonate
Lens Protector	Black ABS
Bracket	Nylon + 30% Glass-Filled
Input Voltage	9-33V DC
Current Raw (@13.5V/@28V) Per Lamp	1.93/0.99

LED's	8
LED Spec	5W CREE LED
Protection	Reverse Polarity Protection, Over and Under Voltage Protection
IP Rating	IP68 & IP69K
Operating Temperature	-40 - +60°
ECE R10	✓
RCM	✓
Warranty	7 Years
Wiring	Red - Positive Yellow - High Beam Trigger Black - Negative
<b>Country of Origin</b>	China
Kit Includes	1 x 10" Single Row Light Bar 1 x Clear Lens Protector 2 x Colour Trims (Electric Blue - fitted on lamp/ Slate Grey - in box) 1 x Wiring Pigtail Lead 1 x EX2 White Position Light Adaptor lead (150mm Brown) Product Instructions S/S Hardware



