



### DESCRIPTION

EX2R's feature ADR Approved white front position lights with RGB technology, offering a choice of 48 colours. With a hybrid beam that provides exceptional width and distance, without dark spots or hot spots, ensuring extraordinary clarity in the dark. Revolutionary internal switching (patent-pending) means there is no need for a harness. Sealed to IP68 & IP69K standards, equipped with hard-coated polycarbonate lenses, composite mounting brackets, stainless steel hardware, and backed by a robust 7-year warranty, the EX2R's are built for long-lasting performance.

Raw Lumens	16800Lm
Effective Lumens	15084Lm
Beam Distance	724m @ 1lux
Beam Width	100m @ 1lux
Colour Temperature	5700K ±5%
Colour Rendering Index (CRI)	70
Height	94
Depth	76.5
Width	780
Weight	3330g ±10%
Cable	2m
Housing	Pressure die-cast aluminium
Lens Material	Hard coated polycarbonate
Lens Protector	Black ABS
Bracket	Nylon + 30% Glass-Filled
Input Voltage	9-33V DC
Current Raw (@13.5V/@28V) Per Lamp	11.1/5.3

LED's	56
LED Spec	5W CREE LED
Protection	Reverse Polarity Protection, Over and Under Voltage Protection
IP Rating	IP68 & IP69K
Operating Temperature	-40 - +60°
ECE R10	✓
RCM	✓
Warranty	7 Years
Wiring	Red - Positive Yellow - High Beam Trigger Black - Negative
Country of Origin	China
Kit Includes	1 x 30" Double Row Light Bar 1 x Clear Lens Protector 2 x Colour Trims (Electric Blue - fitted on lamp/ Slate Grey - in box) 1 x Fused Wiring Harness 1 x EX2 White Position Light Adaptor lead (150mm Brown) Product Instructions S/S Hardware 1 x EX2 12V RGB Controller with 2m lead

