

## ULTIMA 24 INCH LIGHT BAR 71720BK, 71720S, 71725BK & 71725S



CONNECT+



CUSTOM TRIMS



IP68  
IP69K



10 YEAR WARRANTY

### DESCRIPTION

The 24 inch Ultima Light Bar has a market-leading beam pattern that combines beam distance and width with smooth and easy driving. The Ultima Light Bars are engineered to endure heavy-duty conditions, with high ingress protection, improved cooling, and corrosion-resistant and rust-proof brackets. The polycarbonate lens and lens protector are also UV-resistant and protect against stone chips, which allows for a 10 year warranty. The Ultima light bar is customizable with different bezel colors and trims.

### FEATURES AND BENEFITS

- Combination beam
- Uniform beam with no hot spots or dark spots
- Pressure die-cast aluminium housing
- Highest possible ingress protection (IP68 & IP69K)
- Virtually unbreakable polycarbonate lens
- Integrated DT connector with patch harness included
- Interchangeable colour trims
- ADR Approved Front Position light (24 inch) • ECE R10 • CISPR 25 Class 3



### 24 INCH LONG & WIDE HYBRID BEAM P/No.71720BK & 71720S

<b>Input Voltage Range</b>	10-33V DC
<b>Current Draw (@12V)</b>	24A/30A boost
<b>LED Power (Wattage)</b>	325W/390W (boost)
<b>Beam Width</b>	65m
<b>Distance at 1 Lux (Pair)</b>	900m @ 1lux
<b>Lumens (Pair)</b>	16,500Lm/ 18,350Lm (boost)
<b>LED Qty</b>	38
<b>Operating Temperature</b>	-40°C to +60°C
<b>Colour Temperature</b>	5700°K ±5%
<b>Weight</b>	2.8kg ±10%

### 24 INCH ULTRA WIDE FLOOD HYBRID BEAM P/No. 71725BK & 71725S

<b>Input Voltage Range</b>	10-33V DC
<b>Current Draw (@12V)</b>	24A/30A boost
<b>LED Power (Wattage)</b>	325W/390W (boost)
<b>Beam Width</b>	95m
<b>Distance at 1 Lux (Pair)</b>	750m @ 1lux
<b>Lumens (Pair)</b>	16,500Lm/ 18,100Lm (boost)
<b>LED Qty</b>	38
<b>Operating Temperature</b>	-40°C to +60°C
<b>Colour Temperature</b>	5700°K ±5%
<b>Weight</b>	2.8kg ±10%